

# SP3015TF TEMPEST SDIP-27 LEVEL A MONO PRINTER

## Features

- **Fast 40ppm print speed**
- **1200x1200 dpi resolution**
- **USB Interface**
- **Fibre Ethernet Options**
- **IPSEC/IPv6 Option**
- **100,000 page/month duty**
- **SDIP-27 Level A Compliant**



## Description

The SP3015TF TEMPEST Mono Laser printer is the perfect solution for personal or small workgroups where a fast print speed, high-resolution mono printer with multiple interface and security options is required.

The SP3015TF TEMPEST SDIP 27 Level A mono laser printer is based on the HP P3015 printer to provide unparalleled quality, reliability and compatibility. It delivers true 1200 dpi quality at full 40ppm speed, for crisp black text, clear details and superb image quality.

The SP3015TF Printer is configured with high-speed USB 2.0 Port as standard with fibre Ethernet network options including IPSEC traffic encryption. Users can easily retrieve stored confidential print jobs using the control panel's menu and keypad.

The TEMPEST printer retains the functionality and ease of use of the original equipment, including the options of a factory fitted duplex unit and additional 500-sheet paper cassette. The SP3015TF series is compatible with operating systems from Windows 2000/XP to Vista.

The SP3015TF is designed for the most stringent TEMPEST applications requiring compliance to SDIP-27 Level A and compliments the range of TEMPEST products, more details of which can be found at [www.sst.ws](http://www.sst.ws)

# SP3015TF TEMPEST SDIP-27 LEVEL A MONO PRINTER



## PRODUCT SPECIFICATION

### MAIN FEATURES

#### Print Technology

Monochrome Laser

#### Print Quality (black)

1200 x 1200 dpi (black, best quality)

#### Print speed (Black, A4)

Up to 40 ppm (A4 normal)

#### First page out

< 8 seconds from powersave or ready mode

#### Processor Speed

540 MHz

#### Memory

128MB (standard)

640MB (maximum)

#### Recommended monthly page volume

1500 – 5000

#### Duty Cycle (monthly A4)

100,000

#### Interfaces

USB (2.0) (standard)

100Base-FX & 10Base-FL fibre Ethernet options

IPSEC/IPv6 encrypted fibre Ethernet option

#### Print languages

HP PCL 6, HP PCL 5e,

HP Postscript level 3 emulation, direct PDF

### PAPER HANDLING

#### Duplex (double sided printing)

Automatic as standard

#### Paper Handling (input)

100 sheet multipurpose

500 sheet tray

Additional 500 sheet tray options (total 1600)

#### Paper Handling (output)

250 sheet output

100 sheet rear output

#### Standard media sizes

A4, Letter, B5, legal, executive

### TEMPEST

TEMPEST to SDIP-27 Level A

NATO Zone 0 (AMSG720B)

### Compliance

CE Compliant, Energy Star® (duplex version)

IEC 60950, EN 60825, EN61000, EN55024

### ENVIRONMENTAL

#### Physical

Height 316 mm (456 mm with 1 additional tray)

Width 448 mm

Depth 400 mm

Weight 15.9kg approx (21.2kg additional tray)

#### Power

220 – 240 VAC, 50/60Hz

780W (print), 15W (standby) 8.5W (powersave)

#### Temperature

+15°C to +32.5°C (Operating)

-20 °C to 40°C (Storage)

#### Humidity

10 to 80% (Operating, non-condensing)

10 to 90% (Storage, non-condensing)

### OPTIONS

Fibre Ethernet

Additional 500 sheet input paper trays

IPSEC / IPv6 encrypted Fibre Ethernet

Additional memory

Secure Systems & Technologies Ltd	+44 (0)1452 371999	E-mail: <a href="mailto:info@sst.ws">info@sst.ws</a>	<a href="http://www.sst.ws">http://www.sst.ws</a>
Waterwells, Gloucester	E & O E, Subject to change without notice		Issued 01/08/2009
GL2 2AL, England	SP3015TF TEMPEST SDIP-27 Level A Printer Data Sheet 8443-19-001_1.doc		